

MECHANICAL THERMOSTATS



For HTS Ambient Sensing Mechanical Thermostats:

- 22 amp switching current SPDT, 120/250/480 V
- Adjustable Range: 15 to 140°F (-9°C to 60°C)
- Bulb Temperature Limits: -40°F to 160°F (-40°C to 71°C)
- Capillary: 316 Stainless Steel
- Accuracy: +/- 3°F (1.7°C)
- Factory Preset: 40°F (4.4°C)
- Weight: 1.9 lb

For HTS Line Sensing Thermostats:

- 22 amp switching current SPDT, 120/250/480 V
- Adjustable Range: 25 to 140°F (-4°C to 60°C)
- Bulb Temperature Limits: -40°F to 420°F (-40°C to 215°C)
- Capillary: 10' 316 Stainless Steel
- Accuracy: +/- 3°F (1.7°C)
- Factory Preset: 40°F (4.4°C)
- Weight: 1.9 lb



ASTX

DESCRIPTION: High Accuracy Sensing Thermostat
Ordinary Area and Corrosive Environments
UL, CSA & ATEX Approved



LSTX

DESCRIPTION: High Accuracy Line Sensing Thermostat
Ordinary Area and Corrosive Environments
UL, CSA & ATEX Approved



ASTH

DESCRIPTION: High Accuracy Ambient Sensing Thermostat
Explosion-proof; Cl, D1 and 2, Group B, C, D
UL, CSA & ATEX Approved



LSTH

DESCRIPTION: High Accuracy Line Sensing Thermostat
Explosion-proof; Cl, D1 and 2, Group B, C, D
UL, CA & ATEX Approved